
# **Background**

- Dynamic range at transition was showstopper for the 245MHz PLL
- 3D AFE and BBQ appeared to be the solution to this problem
  - Large dynamic range of the diodes they are the first component in the signal path
  - ~160dB suppression of the revolution line plus ~10nm sensitivity
- However, BBQ operates in the coherent spectrum
  - We discover mains harmonics, which are ~50dB more severe in RHIC than Tevatron or SPS
  - We discover the 'anomalous BTF' at injection with ions
  - No obvious solution on the horizon for either of these problems in the coherent spectrum (although there is an APEX proposal to study the anomalous BTF)
  - they both are solid obstacles to making tune feedback operational
- So how about a 'hybrid' system? Direct diode detection of 245MHz pickup
  - preliminary data taken in Run 7 was promising


#### no deliberate beam excitation


# Comparison of 3D AFE Signals from 1m BBQ stripline and resonant 245MHz pickup



#### no deliberate beam excitation


### **Zoom on Betatron Line of Previous Slide**






## Betatron Line with and w/o Excitation


#### with ~20dB kick




#### without kick



## **BTF with Hybrid Tracker**




## **Tune and Amplitude & Phase**




Q2[.]

no perceptible beam decay or emittance growth



time of



Time (Start Fill = 9613)

Beam Decay

# **Summary**

- Preliminary study Dec 30th, parasitic to a RHIC store
  - used the 245MHz signal as LO for mixer chain
  - good beam transfer function measurements
  - good tune tracking
  - no emittance growth
- APEX study Jan 16<sup>th</sup>
  - used multiplied signal from 1m stripline as LO
  - not able to drive the beam
- Parasitic study Jan 20<sup>th</sup>, behind a RHIC store see BBQ elog for details
  - debugged the kicker chain, resolved mixup of pickup planes,...
  - good beam transfer function measurements
  - good tune tracking
  - no emittance growth
  - preliminary measurement of system bandwidth using the 10Hz cryostat vibration line – equal to or better than existing BBQ
- Ready for APEX study
- Ready for ramps?